



# PROTECNET

## WATER-BASED TACKY COATING FOR PROTECTING SURFACES FROM DUST SUCH AS IN PAINT SPRAY BOOTHS

PROTECNET is a 2-in-1 product. It can be used on surfaces such as spray booth walls and paint robots or in any area to:

- protect from paint and varnish or powder.
- create a trap to capture dust.

PROTECNET is an effective solution to prevent air pollution. It can be used directly at the point of dust emission or anywhere where soiling is an issue.

- in paint spray booths where air movement can disperse dust eg from vehicles. It can be applied on floors, walls and tables or even around the filter housing.
- in grinding workshops, storage areas of dusty products, entrances to industrial ovens, , around hoppers etc
- on lights where visibility is required whilst protecting from dust and paint etc.

- \* water-based
- \* contains no solvents nor silicone
- \* authorised for automotive use

### APPLICATION

PROTECNET can be applied by brush, roller, AIRLESS / AIRMIX pump or sprayer on any non-porous, smooth surface (painted metal sheets, light alloys, plastic frames etc). It is used pure and undiluted. Coverage is approximately 10 - 12 m<sup>2</sup>.

Within 15 minutes, the treated surface acquires all requisite adhesive properties to attract and trap dust in contact.

PROTECNET will not lose its “tack” even after long exposure to 80 °C. Loss of efficacy indicates saturation with dust and requires removal before applying a new layer.

Remove PROTECNET easily with a brush, squeegee or high pressure pump, preferably with the addition of our SP260 detergent. Wetting agents in the solution are biodegradable.

SKU 0527 - 5 ltr  
SKU 0528 - 10 ltr

We cannot be held liable for any application or use that does not comply with our instructions